

Want to visualize this product in 3D?

1 Download the  Augment App

2 Scan this image

Global Series Signaling Custom Configured Fixtures

Quick and easy inter-connecting modular products are the best way to describe the Global Series product line.

All combined fixture devices must start with the increased safety "Ex de" models, these units can be combined for a multitude of configurations. The patent pending connecting system greatly simplifies a user's installation and wiring experience by requiring only a single explosion proof wiring gland external to the devices.

Two standard configurations are available pre-assembled from the factory: Linear and Parallel. Other custom configurations are available to meet unique project requirements. Some restrictions apply: contact our Technical Support team or your local sales representative for more options. Devices can include two to six units. For example, the largest configuration offered is a six unit device that is available in all visual or two audible and four visual signals.



Parallel configuration shown

Linear configuration shown

FEATURES

- Fully factory assembled
- Optional 316 stainless steel ratchet adjustable mounting U-bracket for G-MS-C-2B only. (Field assembly required)
- Non-metallic corrosion-resistant GRP housings
- 316 stainless steel dome guard included on visual signals
- Standard M20 cable entries. Select M25 cable entries available
- No mounting orientation limitations
- LED has 8 field selectable flash patterns, default setting to "Flashing at 60 FPM"
- Sounder has 15 field selectable tones, default setting to "C" 1K tone.
- Includes all connector kits/hardware and standard single activation or audio wiring with flying leads. Customer

wiring and activations are available, contact factory for assistance.

- Limited to two audible devices in any single configuration, must locate in Position #1 or #2
- Optional indicator rings are available in six colors: Black, Blue, Green, Magenta, Red and Yellow
- Field customizable legend plates available²
- IP66 enclosure
- Zone 1, 21 Rated, IECEx, ATEX, Ex d IIC, Ex de IIC and Ex tb IIIC
- UL and cUL Listed for Class I, Division 2, Groups A, B, C and D; Class II, Division 1, Groups F and G; and Class III
- Additional custom configurations are available contact Technical Support or a local sales agent for information.



GLOBAL SERIES AUDIBLE PRODUCTS ARE NOT FOR SALE, RE-SALE, DISTRIBUTION OR USE IN THE FOLLOWING COUNTRIES: BELGIUM, FRANCE, GERMANY, ITALY, NETHERLANDS, SPAIN, OR THE UNITED KINGDOM UNTIL AUGUST 2017.

Global Series Signaling Custom Configured Fixtures

G-MSC Linear Configurations

Available from 2 to 6 devices in a linear configuration.
 Devices positions start bottom to top.
 Position #1 determined by proximity to junction box.



G-MSC Parallel Configurations

Available from 2 to 6 devices in a stacked parallel configuration.
 Device positions start bottom left, proceed left to right, then bottom to top.



HOW TO ORDER

- 1- Select a configuration
- 2-Select operating voltage
- 3-Select signal for each position including color for visual products
- 4 -For LED signals select flash pattern, default "Flashing" 60 FPM

- 5-For Sounder signals select tone, default is 1K tone
- Note: audible products must be located in Position 1 or 2 for Linear configurations, or 1, 2, 3, or 4 in Parallel configurations.

GLOBAL SERIES AUDIBLE PRODUCTS ARE NOT FOR SALE, RE-SALE, DISTRIBUTION OR USE IN THE FOLLOWING COUNTRIES: BELGIUM, FRANCE, GERMANY, ITALY, NETHERLANDS, SPAIN, OR THE UNITED KINGDOM UNTIL AUGUST 2017.